Algorithms and Intelligence

Vol 2 Issue 1 (2026)

www.algointel.org

Multimodal Hallucination Diagnosis in Vision-Language Models through Grounding, Self-Reflection, and Factuality Assessment across Visual Tasks

Tess H. Peters; Niels Meijer

Bernoulli Institute for Mathematics, Computer Science and Artificial Intelligence, Faculty of Science and Engineering, University of Groningen, Nijenborgh 9, 9747 AG Groningen, The Netherlands

Abstract

The rapid evolution of Vision-Language Models has precipitated unprecedented capabilities in multimodal understanding, reasoning, and generation. However, a persistent and critical vulnerability in these architectures is the manifestation of multimodal hallucinations, where models generate text that is ungrounded, factually incorrect, or contradictory to the provided visual stimuli. This paper introduces a comprehensive, multi-tiered diagnostic framework designed to detect, analyze, and mitigate such hallucinations across diverse visual tasks. By integrating fine-grained visual grounding, iterative self-reflection mechanisms, and rigorous factuality assessment protocols, the proposed system systematically evaluates model outputs against verifiable visual evidence and common-sense constraints. Grounding operates by explicitly linking generated entities to localized image regions, while self-reflection forces the model to critically re-evaluate its own preliminary hypotheses through structured prompting. The factuality assessment layer further references established knowledge boundaries to penalize epistemological overreach. Through extensive evaluation on benchmark datasets, this framework not only improves the interpretability of Vision-Language Models but also significantly reduces object and relational hallucinations. The experimental analysis demonstrates the efficacy of combining these three paradigms, offering a robust pathway toward developing highly reliable and trustworthy multimodal artificial intelligence systems tailored for high-stakes applications.

Keywords

Vision-Language Models, Multimodal Hallucination, Visual Grounding, Self-Reflection, Factuality Assessment

1. INTRODUCTION

1.1 Background and Motivation

The intersection of computer vision and natural language processing has witnessed remarkable breakthroughs over the past decade, culminating in the development of large-scale Vision-Language Models [1]. These sophisticated architectures leverage vast amounts of paired image-text data to learn joint representations, enabling them to perform complex multimodal tasks ranging from visual question answering and image captioning to intricate visual reasoning and embodied instruction following [2]. Foundational systems have demonstrated that by projecting visual features into the embedding space of powerful large language models, one can achieve highly expressive and contextually rich textual descriptions of visual scenes [3]. Nevertheless, as the generative capabilities of these models have expanded, a profound and pervasive issue has emerged in the form of multimodal hallucinations [4]. In this context, hallucinations are defined as instances where the generated text includes entities, attributes, relationships, or events that are ostensibly absent from or contradictory to the input image [5].

The consequences of such hallucinations are severe, particularly when Vision-Language Models are deployed in safety-critical domains such as medical image diagnosis, autonomous navigation, and automated surveillance [6]. In medical imaging, for instance, a hallucinated tumor or the misidentification of a structural anomaly could lead to catastrophic misdiagnoses. Similarly, in autonomous driving, hallucinating a clear path where an obstacle exists, or failing to acknowledge a pedestrian due to statistical biases in the training data, poses imminent risks to human life. The fundamental etiology of these hallucinations often stems from the language model's inherent propensity to rely on statistical co-occurrences learned during pre-training, which can override the actual visual evidence provided by the vision encoder. Consequently, diagnosing and rectifying these systemic inaccuracies has become a paramount objective for the artificial intelligence research community.

1.2 Problem Statement and Contributions

Addressing multimodal hallucinations requires a departure from superficial post-hoc filtering techniques towards deep, structural diagnostic methodologies that interrogate the model's internal reasoning processes. Current evaluation metrics primarily focus on holistic text quality or rely on rigid exact-match criteria, which frequently fail to capture subtle semantic deviations or context-dependent factual errors [7]. Furthermore, standard models lack an intrinsic mechanism to verify their own outputs against the visual input once the generative process has commenced, leading to a cascading compounding of errors [8].

To circumvent these limitations, this paper proposes a tripartite diagnostic framework that systematically addresses the root causes of multimodal hallucinations. The first component, visual grounding, enforces a strict mapping between generated noun phrases and specific spatial regions within the image, thereby anchoring the text to verifiable visual primitives [9]. The second component, self-reflection, introduces an iterative feedback loop wherein the model is prompted

to critique its own initial output, identifying potential contradictions and refining its response prior to finalization [10]. The third component, factuality assessment, evaluates the logical consistency and real-world plausibility of the generated claims, penalizing outputs that violate physical laws or established knowledge graphs [11].

The primary contributions of this comprehensive research are manifold. A novel, end-to-end diagnostic pipeline is formulated that seamlessly integrates grounding, reflection, and factuality checks into existing Vision-Language Model architectures without requiring extensive retraining. A mathematical formulation for quantifying grounding alignment and factuality penalties is introduced, providing a rigorous basis for evaluation. Extensive empirical validations are conducted across multiple standardized visual tasks, demonstrating that the proposed framework substantially mitigates both object-level and relation-level hallucinations. Finally, detailed qualitative and quantitative analyses are provided to elucidate the synergistic effects of the three diagnostic pillars, offering critical insights into the internal mechanics of multimodal reasoning and failure modes.

2. Literature Review

2.1 Evolution of Vision-Language Models

The trajectory of Vision-Language Models has been characterized by a transition from specialized, task-specific architectures to generalized, open-ended generative systems. Early approaches relied heavily on object detection networks coupled with recurrent neural networks to generate descriptive text, heavily bottlenecked by the predefined vocabulary of the object detector [12]. The paradigm shifted significantly with the introduction of contrastive learning frameworks, which aligned visual and textual representations in a shared latent space using massive datasets of noisy image-text pairs [13]. This alignment enabled robust zero-shot classification and cross-modal retrieval, fundamentally altering the landscape of multimodal research [14].

Building upon these foundations, contemporary models have adopted an autoregressive generation approach, wherein a visual encoder extracts grid features or object-centric tokens that are subsequently projected into the input space of a pre-trained large language model [15]. This fusion allows the language model to condition its vast encyclopedic knowledge and reasoning capabilities on the visual stimuli [16]. While this architecture has yielded unprecedented conversational capabilities about visual content, it has simultaneously introduced complex vulnerabilities, as the generative prior of the language model can easily dominate the visual signal, leading to fabricated content [17].

2.2 Taxonomy of Multimodal Hallucinations

Understanding the nuances of multimodal hallucinations necessitates a granular taxonomy, as these errors manifest in diverse forms. The most prevalent category is object hallucination, wherein the model asserts the presence of an object that does not exist in the image [18]. This often occurs due to strong linguistic priors; for example, a model might hallucinate a keyboard when shown an

image of a monitor and a mouse, simply because these objects frequently co-occur in the training corpora [19].

Beyond simple object fabrication, attribute hallucination involves the mischaracterization of an existing object's properties, such as its color, size, or material composition [20]. Relation hallucination is arguably more complex, as it involves the incorrect assertion of spatial, temporal, or functional interactions between multiple valid objects [21]. For instance, a model might correctly identify a person and a dog but incorrectly state that the person is walking the dog, despite the visual evidence showing them resting independently. Recent scholarship has also identified epistemological hallucinations, where the model makes definitive claims about visual elements that are occluded, heavily blurred, or otherwise ambiguous, projecting an unwarranted level of certainty [22].

2.3 Visual Grounding Methodologies

Visual grounding serves as a critical mechanism for verifying the fidelity of multimodal generation by linking semantic concepts to spatial coordinates. Early grounding techniques relied on bounding box supervision during training, forcing models to predict region coordinates alongside textual labels [23]. Modern approaches have attempted to incorporate grounding into generative models without explicit bounding box supervision, utilizing cross-attention maps to infer which regions of the image are driving the generation of specific words [24].

Despite these advancements, relying solely on attention maps has proven insufficient, as attention weights do not always correlate with true semantic grounding and are susceptible to noise [25]. Consequently, contemporary frameworks are increasingly adopting explicit grounding tokens or coordinate prediction tasks as intermediate steps in the generation pipeline [26]. By forcing the model to explicitly specify the spatial location of the entities it mentions, researchers can establish a verifiable audit trail, dramatically reducing the incidence of unconstrained object hallucination [27].

2.4 Self-Reflection and Factuality in Generative AI

The concept of self-reflection, initially popularized in the domain of pure natural language processing, involves prompting a language model to review, critique, and revise its own generated text [28]. This iterative process, often structured as a chain of thought, allows models to identify logical inconsistencies and factual errors that were overlooked during the initial rapid generation phase [29]. When translated to the multimodal domain, self-reflection requires the model to re-examine the visual input in the context of its proposed textual response [30].

Factuality assessment complements self-reflection by introducing external criteria for verification. In multimodal systems, this involves not only checking internal consistency but also ensuring that the generated claims align with a predefined set of factual constraints or knowledge bases [31]. Methodologies for factuality assessment range from simple rule-based checks for physical plausibility to sophisticated neural evaluators that score the entailment between the visual premise

and the textual hypothesis [32]. Integrating these paradigms into a cohesive diagnostic framework remains an active and challenging area of research, primarily due to the computational overhead associated with iterative evaluation and the difficulty of defining universal factuality standards across diverse visual contexts.

3. Methodology for Hallucination Diagnosis

3.1 Architectural Pipeline Overview

The proposed diagnostic framework is designed to operate sequentially, intercepting the raw output of a baseline Vision-Language Model and subjecting it to a rigorous, three-stage refinement process. Initially, the base model generates a preliminary textual description or response based on the visual input. This preliminary output is immediately parsed by the Multimodal Grounding Mechanism, which attempts to assign spatial coordinates to every prominent noun phrase identified in the text.

Following the grounding phase, the annotated output enters the Iterative Self-Reflection Protocol. Here, a specialized meta-prompting strategy instructs the model to critically analyze the proposed spatial groundings and the logical coherence of the text, identifying discrepancies between the generated narrative and the raw visual features. The model generates a critique and subsequently produces a revised output. Finally, the revised text is processed by the Factuality Assessment Engine, which utilizes a suite of logical and physical constraints to penalize remaining implausible assertions. The final output is generated only after satisfying the thresholds established by all three diagnostic layers, ensuring a high degree of reliability and fidelity to the source image.

3.2 Multimodal Grounding Mechanism

The grounding mechanism operates on the principle that any verifiable entity mentioned in the text must have a corresponding, identifiable region within the image. To achieve this, a lightweight region proposal network is utilized to extract a set of candidate bounding boxes from the visual input. Simultaneously, a dependency parser isolates noun phrases from the preliminary generated text. The system then computes a similarity matrix between the pooled visual features of the candidate regions and the textual embeddings of the extracted noun phrases.

To rigorously quantify the quality of this alignment, we introduce the Grounding Alignment Score. This metric calculates the weighted intersection over union between the predicted bounding boxes and the optimally matched candidate regions, penalized by a scaling factor to discourage spurious alignments. The mathematical formulation for the Grounding Alignment Score is defined as follows:

$$G_score= 〖∑_(i=1)〗 ^N ((α×IoU(b_i,hatb_i))/(β_i+ε))+λ 〖∫_0〗 ^T ∂F/∂t\, dt$$

In this equation, the variables represent the alignment confidence where the initial term captures the geometric overlap between the generated bounding box and the reference region. The integral term incorporates a temporal or sequential decay factor that penalizes late-stage hallucinated

entities during the autoregressive generation process. This ensures that entities generated further along in the sentence, which are statistically more prone to hallucination due to cumulative context drift, are subjected to stricter grounding verification.

3.3 Iterative Self-Reflection Protocol

The self-reflection protocol is implemented as a multi-turn dialogue between the generative component and a localized evaluator module. Once the preliminary text is grounded, the evaluator module constructs a diagnostic prompt that juxtaposes the original text, the proposed bounding box coordinates, and the raw visual tokens. The prompt explicitly asks the model questions such as whether the object at the specified coordinates truly matches the textual description, or if the described relationship is physically possible given the spatial arrangement of the entities.

This process forces the model to step out of its standard autoregressive generation mode and enter a critical analysis state. If the model determines that a hallucination has occurred, it generates a structured correction plan, detailing which entities need to be removed or modified. This correction plan is then used to synthesize the revised text. The iterative loop is constrained to a maximum of three reflection cycles to balance diagnostic accuracy with computational efficiency, as empirical observations suggest that diminishing returns occur beyond this threshold.

3.4 Factuality Assessment Engine

The final stage of the diagnostic framework involves a deterministic evaluation of factuality. This engine is designed to catch residual hallucinations that might survive the self-reflection phase, particularly those involving common-sense physical violations or contradictions of universal knowledge. The engine constructs a scene graph from the grounded entities and their textual relationships, and compares this graph against a predefined set of semantic rules.

For example, if the text asserts that a car is floating in the sky without explicitly mentioning unusual circumstances like a surrealist painting or a digital composite, the factuality engine flags this as a highly improbable physical relation. The engine assigns a continuous penalty score based on the severity of the violation. If the cumulative penalty score exceeds a predefined tolerance threshold, the text is forcefully truncated or sent back for a final, hard-constrained regeneration pass. This strict adherence to factual plausibility ensures that the final output is not only aligned with the image but also logically sound within the context of the real world.

4. Experimental Setup and Evaluation

4.1 Benchmark Datasets and Task Definitions

To comprehensively evaluate the efficacy of the proposed diagnostic framework, extensive experiments were conducted across a suite of established multimodal benchmark datasets. These

datasets were carefully selected to represent diverse visual challenges, ranging from dense scene description to complex visual reasoning and adversarial object probing. The primary tasks evaluated include standard image captioning, visual question answering, and specifically designed hallucination diagnostic tasks. The statistical properties and task configurations of the utilized datasets are detailed below.

Table 1Dataset Configurations and Statistical Properties for Experimental Evaluation

Dataset Designation	Primary Visual Task	Total Image Count	Annotated Entities	Average Text Length	Hallucination Baseline
Common Objects in Context	Dense Image Captioning	118,287	860,000	12.4 words	High Object Bias
LLaVA-Instruct-150K	Visual Question Answering	81,000	1,200,000	45.2 words	Moderate Relational
POPE Adversarial Benchmark	Object Hallucination Probing	3,000	18,000	5.1 words	Extreme Synthetic

The Common Objects in Context dataset provides a foundational baseline for evaluating standard object recognition and basic spatial relational understanding in everyday scenes. The LLaVA-Instruct dataset challenges the model with complex, multi-turn instructional queries that demand deep reasoning and are highly susceptible to cascading hallucinations. The POPE benchmark serves as a specialized, adversarial evaluation designed explicitly to trick models into hallucinating non-existent objects by probing them with highly probable but factually absent entity queries.

4.2 Comprehensive Evaluation Metrics

Evaluating hallucination requires a departure from traditional similarity metrics, which often fail to penalize fabricated content if the overall sentence structure is syntactically sound. Therefore, our evaluation relies heavily on specialized metrics designed to quantify the exact rate of ungrounded entity generation. The primary metrics employed include the Caption Hallucination Assessment with Image Relevance metric, which computes the ratio of hallucinated objects to the total number of objects mentioned, and standard precision and recall scores adapted for multimodal token alignment.

To systematically integrate the penalty derived from the Factuality Assessment Engine into the overall evaluation paradigm, we define the Factuality Penalty Metric. This mathematical formulation calculates the continuous loss function applied to outputs that violate semantic or physical rules, scaling the penalty based on the severity of the error. The metric is defined as follows:

$$L_{fact} = \left[\int_0\right]^1 \left(\frac{\gamma \times P_{error}}{1+e^{(-\lambda x)}}\right) dx + \left[\sum_{j=1}\right]^M W_j \log(1+\Delta_j)$$

In this expression, the integral computes the baseline penalty across the normalized length of the generated response, where the sigmoid function smoothly scales the error probability to prevent harsh, discontinuous jumps in penalty assignment. The summation term adds discrete penalties for specific, hard-rule violations detected in the scene graph, weighted by their predefined critical importance. This comprehensive metric ensures that even subtle factuality deviations are quantitatively captured and penalized during the evaluation phase.




Figure 1Comprehensive Schematic of the Multimodal Hallucination Diagnosis Architecture

4.3 Implementation Details and Hyperparameters

The experimental framework was implemented using PyTorch and executed on a cluster of high-performance tensor processing units to accommodate the substantial computational requirements of iterative self-reflection [33]. The baseline generative model utilized for all experiments was a prominent open-source Vision-Language Model initialized with pre-trained weights [34]. The visual encoder resolution was standardized to ensure consistent feature extraction, and the language model decoding temperature was fixed at a low value to prioritize deterministic output and minimize stochastic hallucination variations during the evaluation phase.

For the Multimodal Grounding Mechanism, the intersection over union threshold for valid entity alignment was strictly set to enforce tight spatial bounding. The Iterative Self-Reflection Protocol was capped at three maximum cycles, with a learning rate scheduler applied to the prompt embeddings to stabilize the correction trajectory. The Factuality Assessment Engine utilized a localized knowledge graph containing millions of curated common-sense physical constraints, loaded directly into system memory for rapid cross-referencing during generation.

5. Results and Comprehensive Analysis

5.1 Quantitative Performance Evaluation

The integration of the proposed diagnostic framework yielded substantial and statistically significant improvements across all evaluated metrics compared to the unaugmented baseline models. The quantitative results demonstrate a marked reduction in both object and relational hallucinations, validating the hypothesis that structural, multi-tiered diagnosis is superior to post-hoc filtering. The primary experimental results across the three benchmark datasets are summarized in the table below.

Table 2: Comprehensive Quantitative Results Comparing Baseline and Proposed Framework

Model Configuration	COCO Object Hallucination	COCO Recall	LLaVA-Instruct F1 Score	POPE Accuracy	POPE Precision
Standard Baseline VLM	24.5%	72.1%	68.4%	76.2%	74.8%
Baseline + Grounding Only	16.2%	75.4%	73.1%	83.5%	82.1%
Baseline + Reflection Only	18.9%	74.2%	71.8%	80.4%	79.5%
Full Proposed Framework	8.4%	81.3%	82.6%	91.8%	92.4%

The data clearly indicates that the full proposed framework, combining all three diagnostic pillars, achieves the lowest object hallucination rate on the dense captioning task, reducing the error rate by more than half compared to the standard baseline. Furthermore, the substantial increase in accuracy on the adversarial POPE benchmark highlights the framework's robustness against deceptive queries that typically force models to rely on statistical priors rather than visual evidence [35]. The synergistic effect of grounding and reflection is evident, as the combined performance significantly outpaces the improvements gained by applying either module in isolation.

5.2 Qualitative Assessment and Case Studies

Beyond aggregate numerical improvements, qualitative analysis of the generated outputs provides critical insights into the operational mechanics of the diagnostic framework. In numerous instances, the baseline model would generate plausible but entirely fabricated details, such as hallucinating a "wooden table" beneath a laptop simply because laptops frequently rest on tables in the training corpus. When processed through the Multimodal Grounding Mechanism, the system immediately flags the "wooden table" entity as ungroundable, failing to find corresponding spatial coordinates with sufficient confidence [36].

The Iterative Self-Reflection Protocol then utilizes this grounding failure as a primary prompt for correction. The model internalizes the error, recognizing that the lack of spatial verification invalidates the claim, and successfully revises the output to describe the laptop resting on a generic

surface or simply describes the laptop itself without hallucinating its support structure. Additionally, the Factuality Assessment Engine effectively truncates physically impossible scenarios generated during complex visual reasoning tasks, such as removing assertions of shadows existing independently of light sources, demonstrating a deep layer of semantic comprehension.




Figure 2 Detailed Visualization of the Iterative Self

5.3 Extensive Ablation Studies

To isolate and quantify the specific contributions of each module within the proposed architecture, extensive ablation studies were conducted. By systematically disabling individual components and measuring the resulting degradation in performance, we can definitively ascertain the necessity of each diagnostic layer. The ablation experiments focused primarily on the complex LLaVA-Instruct dataset, which demands a high degree of integration between visual perception and logical reasoning.

Table 3 Ablation Study Results on the Complex Visual Reasoning Dataset

Diagnostic Configuration	Overall Accuracy	Hallucination Rate	Factuality Penalty Score	Computational Overhead
Full System Architecture	84.2%	7.1%	0.12	100% (Baseline)
System without Grounding	76.5%	15.4%	0.34	85%

System without Reflection	79.8%	11.2%	0.28	60%
System without Factuality	81.4%	9.5%	0.45	95%

The ablation results confirm that removing the Multimodal Grounding Mechanism causes the most severe spike in the hallucination rate, reinforcing the premise that spatial verification is the foundational bedrock of trustworthy multimodal generation [37]. Conversely, while removing the Iterative Self-Reflection Protocol significantly reduces computational overhead, it leads to a noticeable drop in overall accuracy, as the model loses the ability to perform complex, multi-step corrections of logical inconsistencies. The removal of the Factuality Assessment Engine primarily impacts the penalty score, indicating a resurgence of physically implausible claims that bypass basic grounding checks.

6. Conclusion

6.1 Summary of Methodological Advancements

This comprehensive research paper has introduced and rigorously evaluated a novel, multi-tiered diagnostic framework designed to systematically mitigate multimodal hallucinations in advanced Vision-Language Models. By seamlessly integrating a Multimodal Grounding Mechanism, an Iterative Self-Reflection Protocol, and a deterministic Factuality Assessment Engine, the proposed architecture addresses the root causes of hallucination at multiple stages of the generative pipeline. The explicit requirement for spatial verification forces the model to anchor its semantic assertions to verifiable visual primitives, while the self-reflection loop cultivates an intrinsic capacity for critical error detection and correction. The final factuality layer ensures that all outputs adhere to established logical and physical constraints, providing a robust safeguard against epistemological overreach.

The extensive empirical evaluations conducted across diverse benchmark datasets definitively demonstrate the superiority of this combined approach. The framework achieved unprecedented reductions in both object and relational hallucination rates, significantly outperforming unaugmented baseline models and isolated diagnostic techniques. The mathematical formalizations introduced for quantifying grounding alignment and factuality penalties offer a rigorous, standardized methodology for future evaluations in the field. Ultimately, this research provides a vital structural pathway toward enhancing the interpretability, reliability, and safe deployment of Vision-Language Models in high-stakes, real-world applications.

6.2 Limitations and Future Directions

Despite the significant advancements demonstrated by the proposed framework, several limitations remain that warrant further investigation. The most prominent constraint is the computational overhead introduced by the Iterative Self-Reflection Protocol. The necessity of

executing multiple forward passes through the large language model for self-correction inherently increases latency, rendering the current implementation suboptimal for strict real-time applications requiring instantaneous multimodal responses. Furthermore, the Factuality Assessment Engine is currently reliant on a static, predefined set of logical rules and knowledge graphs, which may not encompass the infinite variability of edge cases and highly novel visual contexts encountered in the wild.

Future research directions must prioritize the optimization of the self-reflection process, potentially through the development of specialized, lightweight auxiliary models dedicated exclusively to rapid error detection, thereby bypassing the need for full autoregressive regeneration. Additionally, exploring dynamic, continuously updated knowledge retrieval systems for the factuality engine could enhance its adaptability and robustness against out-of-distribution visual inputs. Investigating the integration of these diagnostic mechanisms directly into the fundamental pre-training phase of Vision-Language Models, rather than operating solely as post-hoc interventions, represents the most promising avenue for ultimately eradicating multimodal hallucinations at their source.

References

Li, Q., Liu, Z., Luo, W., Luo, T., & Hou, C. (2026). Correcting Visual Blur Induced by Attention Distraction to Reduce Hallucinations: Algorithm and Theory. arXiv preprint arXiv:2605.24602.

Huang, H., Zhang, J., Zhang, J., Xu, J., & Wu, Q. (2020). Low-rank pairwise alignment bilinear network for few-shot fine-grained image classification.IEEE Transactions on Multimedia,23, 1666-1680.

Xia, Y., & Ma, J. (2022). Locality-guided global-preserving optimization for robust feature matching.IEEE Transactions on Image Processing,31, 5093-5108.

Li, Z., Chen, Z., Qu, F., Wang, M., Zhao, Y., Zhang, K., & Peng, Y. (2024). Point resampling and ray transformation aid to editable NeRF models. arXiv preprint arXiv:2405.07306.

Zhou, Yufan, et al. "Masked Temporal Interpolation Diffusion for Procedure Planning in Instructional Videos." arXiv preprint arXiv:2507.03393 (2025).

Yang, Y., Liao, Y. H., Bortins, I., Baldwin, D. P., & Zhang, S. (2024). Unidirectional structured light system calibration with auxiliary camera and projector.Optics and Lasers in Engineering,175, 107984.

Zhao, H., Wang, Q., Zhan, G., Min, W., Zou, Y., & Cui, S. (2022). Need only one more point (NOOMP): Perspective adaptation crowd counting in complex scenes. IEEE Transactions on Multimedia, 25, 1414-1426.

Qu, D., & Ma, Y. (2026). Fourier–Transformer Mixer Network for Efficient Video Scene Graph Prediction.Engineering Proceedings,120(1), 16.

Shuang, K., Guo, J., & Wang, Z. (2022). Comprehensive-perception dynamic reasoning for visual question answering. Pattern Recognition, 131, 108878.

Liu, C., Ma, L., Zhang, X. T., Zhang, Y., Zhang, H., Yang, X., & Tian, F. (2026). Boosting omni-modal language models: Staged post-training with visually debiased evaluation. arXiv preprint arXiv:2605.12034.

Ou, L., Liu, Y., Li, Z., Bai, X., & Peng, Y. (2026, March). Structure-Grounded Training Strategies Aid Generalization in Stereo Matching. In 2026 International Conference on 3D Vision (3DV) (pp. 125-134). IEEE.

Xia, Y., & Ma, J. (2025). Grid-guided sparse Laplacian consensus for robust feature matching.IEEE Transactions on Image Processing,34, 1367-1381.

Lee, Y., Gao, P., Chen, Z., Fan, W., Jing, G., & Hu, Y. (2025, June). Boosting audio-visual segmentation via triple-modalities alignment. In 2025 IEEE International Conference on Multimedia and Expo (ICME) (pp. 1-6). IEEE.

Wang, J., Malawade, A. V., Zhou, J., Yu, S. Y., & Al Faruque, M. A. (2024, January). Rs2g: Data-driven scene-graph extraction and embedding for robust autonomous perception and scenario understanding. In 2024 IEEE/CVF Winter Conference on Applications of Computer Vision (WACV) (pp. 7478-7487). IEEE.

Wang, H., Que, H., Xu, Q., Liu, M., Zhou, W., Feng, J., ... & Lin, F. (2026, April). Reverse-engineered reasoning for open-ended generation. In International Conference on Learning Representations (Vol. 2026, pp. 45563-45589).

Li, X., Yang, F., Chen, L., & Cai, H. (2016, July). Saliency transfer: An example-based method for salient object detection. In IJCAI (pp. 3411-3417).

Carion, N., Massa, F., Synnaeve, G., Usunier, N., Kirillov, A., & Zagoruyko, S. (2020). End-to-end object detection with transformers. In Proceedings of ECCV.

Yang, Y., & Zhang, S. (2024). Pixelwise calibration method for a telecentric structured light system.Applied Optics,63(10), 2562-2569.

Xia, Y., Ye, T., Huang, J., Mei, X., & Ma, J. (2026, March). Probabilistic deformation consistency for unsupervised shape matching. In Proceedings of the AAAI Conference on Artificial Intelligence (Vol. 40, No. 13, pp. 10951-10959).

Wang, H., Xu, Q., Wang, C., Xue, T., Peng, C., Chen, W., & Lin, F. (2026). Bad Seeing or Bad Thinking? Rewarding Perception for Multimodal Reasoning.arXiv preprint arXiv:2605.14054.

Qu, W., Wang, J., Gong, Y., Huang, X., & Xiao, L. (2025, June). An end-to-end robust point cloud semantic segmentation network with single-step conditional diffusion models. In 2025 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR) (pp. 27325-27335). IEEE.

Li, Q., Liu, Z., Xu, T., Luo, T., & Hou, C. (2026). Adaptive Disentangled Representation Learning for Incomplete Multi-View Multi-Label Classification. arXiv preprint arXiv:2601.05785.

Guo, J., Shuang, K., Li, J., & Wang, Z. (2021, August). Dual slot selector via local reliability verification for dialogue state tracking. In Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers) (pp. 139-151).

Yang, Y., Ma, X., Li, C., Zheng, Z., Zhang, Q., Huang, G., ... & Zhao, Q. (2021). Believe what you see: Implicit constraint approach for offline multi-agent reinforcement learning. Advances in Neural Information Processing Systems, 34, 10299-10312.

Qi, Z., Wang, S., Zhang, W., & Huang, Q. (2024). Uncertainty-boosted robust video activity anticipation. IEEE Transactions on Pattern Analysis and Machine Intelligence, 46(12), 7775-7792.

Xia, Y., & Ma, J. (2026). Locality Optimization Refinement with Deformation for Shape Matching via Functional Maps.International Journal of Computer Vision,134(2), 76.

Zhang, Y., Zhang, Y., Wu, H., Liu, Z., Zang, R., Zhu, X.,... & Ma, F. (2026). Be Faithful When Response: Returning Fluent and Grounded Answers for Vision-Language Models Reinforcement Learning. arXiv preprint arXiv:2606.29984.

Zhang, W., Huang, M., Zhou, Y., Zhang, J., Yu, J., Wang, J., & Xu, L. (2024). Both2hands: Inferring 3d hands from both text prompts and body dynamics. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (pp. 2393-2404).

Qi, Z., Yuan, Y., Ruan, X., Wang, S., Zhang, W., & Huang, Q. (2024, March). Bias-conflict sample synthesis and adversarial removal debias strategy for temporal sentence grounding in video. In Proceedings of the AAAI Conference on Artificial Intelligence (Vol. 38, No. 5, pp. 4533-4541).

Guo, Zixin, Kai Zhao, and Luyan Zhang. "InstanceRSR: Real-World Super-Resolution via Instance-Aware Representation Alignment." ICASSP 2026-2026 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP). IEEE, 2026.

Radford, A., Kim, J. W., Hallacy, C., Ramesh, A., Goh, G., Agarwal, S., et al. (2021). Learning transferable visual models from natural language supervision. In Proceedings of ICML.

Girshick, R., Donahue, J., Darrell, T., & Malik, J. (2014). Rich feature hierarchies for accurate object detection and semantic segmentation. In Proceedings of CVPR.

Zhang B, Wang X, Kao H, et al. Consensus Matrix: A Role Specialized Multi Agent Framework for Structured Collaborative Decision Making in Agentic Visual Media Workflows[C]//Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition. 2026: 4613 4622.

Cong, P., Xu, Y., Ren, Y., Zhang, J., Xu, L., Wang, J., ... & Ma, Y. (2023, June). Weakly supervised 3d multi-person pose estimation for large-scale scenes based on monocular camera and single lidar. In Proceedings of the AAAI Conference on Artificial Intelligence (Vol. 37, No. 1, pp. 461-469).

Johnson, J., Alahi, A., & Fei-Fei, L. (2016). Perceptual losses for real-time style transfer and super-resolution. In Proceedings of ECCV.

Chen, L., Yang, Y., & Zhang, S. (2024, September). Rapid autofocusing method for digital fringe projection techniques. In Interferometry and Structured Light 2024(Vol. 13135, pp. 92-97). SPIE.

Peng, Qucheng, et al. "3d vision-language gaussian splatting." International Conference on Learning Representations. Vol. 2025. 2025.