Algorithms and Intelligence

Vol 2 Issue 1 (2026)

www.algointel.org

Memory-Bank Calibration for Localized Visual Novelty under Background Shift

Alaa Hussein

Mechatronics Engineering Department, Faculty of Engineering, Ain Shams University, Cairo, Egypt

Abstract

The detection of localized visual novelty remains a critical challenge in computer vision, particularly when operating within unstructured environments characterized by significant background shift. Traditional anomaly detection models often assume a static background distribution, leading to a high rate of false positives when faced with varying illumination, weather conditions, or sensor perturbations. This paper introduces a comprehensive memory-bank calibration framework designed to decouple localized anomalous features from global environmental variations. By leveraging a dynamically updated feature repository, the proposed system continuously calibrates its reference distribution to reflect the current background state, thereby isolating genuine structural or semantic novelties. We detail the system architecture, which extracts deep hierarchical features and maps them into a spatially aware memory bank. Furthermore, a novel calibration mechanism is introduced that operates directly in the latent space, adjusting the stored normative representations based on contextual background cues without requiring computationally expensive retraining. Extensive theoretical analysis and qualitative evaluations demonstrate that this calibration approach significantly mitigates the impact of background shift, enhancing both the precision and robustness of novelty localization. The findings present a paradigm shift in how memory-augmented neural networks handle non-stationary environments, offering scalable solutions for industrial inspection, autonomous navigation, and environmental monitoring.

Keywords

Visual Novelty Detection, Memory Bank, Background Shift, Anomaly Localization, Dynamic Calibration

1. INTRODUCTION

The capacity to identify visual novelty is a fundamental requirement for autonomous systems operating in dynamic, real-world environments. Visual novelty detection refers to the algorithmic process of identifying regions within an image or video stream that deviate significantly from a learned normative baseline. This capability is paramount across a wide spectrum of applications,

ranging from identifying manufacturing defects in industrial quality control to detecting unexpected obstacles in autonomous driving scenarios and recognizing pathological anomalies in medical imaging [1, 2]. In ideal, controlled settings, traditional models can establish a highly accurate representation of normality. However, when these models are deployed in unconstrained environments, they frequently encounter the phenomenon of background shift. Background shift describes the systemic and often benign variation in the global environmental context, such as changes in ambient illumination, seasonal weather variations, camera perspective shifts, and sensor noise patterns [3, 4]. These shifts fundamentally alter the statistical distribution of the visual data, causing static models to misinterpret harmless environmental changes as critical anomalies.

The primary challenge in this domain is distinguishing between localized visual novelty and global background shift. Localized novelty implies a discrete, spatially bounded anomaly that is semantically relevant to the task at hand, such as a physical crack on a mechanical component or an unauthorized object on a secure perimeter [5, 6]. Conversely, background shift is typically a pervasive, image-wide transformation that does not inherently constitute a structural defect or semantic threat. When a computer vision system lacks the sophisticated mechanisms required to decouple these two phenomena, the result is an overwhelming influx of false positive detections [7]. These false positives degrade system reliability, trigger unnecessary alarms, and ultimately erode the trust of human operators relying on automated monitoring systems. Addressing this challenge necessitates the development of adaptive algorithms that can dynamically recalibrate their understanding of normality based on the shifting environmental context. Recent advancements in deep learning have popularized the use of memory-augmented neural networks for anomaly detection. Memory banks, in particular, have emerged as a powerful tool for storing explicit representations of normal features extracted from a training dataset [8, 9]. During the inference phase, the system extracts features from the test image and compares them against the stored normative features in the memory bank. If the distance between the test features and the nearest items in the memory bank exceeds a predefined threshold, the region is flagged as anomalous. This approach offers significant advantages over purely generative or reconstructive models, as it provides a deterministic and interpretable mechanism for novelty scoring. However, conventional memory banks are fundamentally static. Once populated during the training phase, their contents remain fixed, anchoring the system to the specific environmental conditions present in the training data [10, 11]. Consequently, standard memory bank architectures are highly vulnerable to background shift, as any deviation in the global environment will increase the distance between the extracted features and the stored memory items, regardless of whether a true localized anomaly is present. To bridge this critical gap in the existing literature, this paper proposes a novel framework centered on memory-bank calibration. The core hypothesis is that the normative feature representations stored within a memory bank can be dynamically adjusted in the latent space to align with the current background context, thereby preserving the system's sensitivity to localized novelties while suppressing the noise generated by global shifts [12, 13]. This calibration process operates without the need for continuous, computationally intensive network retraining, making it highly suitable for real-time deployment in resource-constrained environments. By introducing a mechanism that continuously analyzes the global feature distribution of incoming visual data and applies a corresponding transformation to the memory bank contents, the proposed framework establishes a resilient baseline for anomaly scoring.

The subsequent sections of this paper provide a comprehensive exploration of the proposed methodology and its theoretical underpinnings. Section 2 offers an extensive review of the relevant literature, tracing the evolution of anomaly detection techniques and highlighting the specific challenges posed by non-stationary environments. Section 3 details the overall system architecture, including the deep feature extraction pipeline and the construction of the spatially aware memory

bank. Section 4 presents the mathematical and algorithmic intricacies of the memory-bank calibration mechanism, explaining how global contextual cues are utilized to modulate the stored feature representations. Section 5 discusses the experimental setup, provides a thorough analysis of the quantitative and qualitative results, and explores the limitations of the proposed approach. Finally, Section 6 summarizes the key contributions of the research and outlines promising directions for future investigation in the field of adaptive visual novelty detection.

2. Literature Review and Background

2.1 Evolution of Visual Novelty Detection

The field of visual novelty detection has undergone a dramatic transformation over the past two decades, evolving from simple statistical thresholding techniques to complex, deep learning-based architectures. Early approaches relied heavily on handcrafted feature descriptors, such as scale-invariant feature transforms and histograms of oriented gradients, coupled with traditional machine learning classifiers like support vector machines and random forests [14, 15]. While these methods achieved moderate success in highly constrained environments with static lighting and fixed camera angles, they lacked the representational capacity to handle the high dimensionality and immense variability of real-world visual data. The reliance on handcrafted features meant that these systems were intrinsically brittle, failing to generalize across different anomaly types or environmental conditions. The advent of deep learning introduced a paradigm shift, enabling systems to automatically learn hierarchical feature representations directly from raw pixel data. Autoencoders and their variational counterparts became the standard architecture for unsupervised anomaly detection [16, 17]. These reconstructive models operate on the principle that a network trained exclusively on normal data will successfully reconstruct normal inputs but will fail to accurately reconstruct anomalous regions. The discrepancy between the input image and the reconstructed image, often quantified using simple pixel-wise distance metrics, serves as the anomaly score. Despite their conceptual elegance, reconstructive models suffer from significant limitations. Deep autoencoders possess a remarkable capacity for generalization, which can inadvertently lead to the successful reconstruction of anomalous inputs, thereby masking the novelty [18, 19]. Furthermore, pixel-wise reconstruction errors are highly sensitive to minor spatial misalignments and changes in illumination, making them particularly vulnerable to the types of background shifts addressed in this research. To overcome the limitations of reconstructive models, researchers began exploring feature-matching techniques that operate in the latent space of pre-trained convolutional neural networks. These methods extract dense feature maps from both the training and testing datasets using robust architectures such as residual networks [20, 21]. The underlying assumption is that pre-trained networks, exposed to vast and diverse datasets during their initial training, capture highly discriminative semantic features. Anomaly detection then becomes a problem of density estimation or distance calculation within this high-dimensional feature space. While feature-matching techniques demonstrate superior robustness to minor spatial variations compared to pixel-wise reconstruction, they remain susceptible to domain gaps. If the distribution of the target environment differs significantly from the distribution of the dataset used to pre-train the feature extractor, the resulting feature representations may lack the specificity required for accurate novelty localization [22, 23].

2.2 Challenges of Background Shift in Computer Vision

Background shift represents a profound challenge for any computer vision system that relies on establishing a static baseline of normality. In the context of visual novelty detection, a background shift occurs when the underlying data generating process experiences a systematic change that

affects the entire visual scene but does not inherently constitute an anomaly. These shifts are pervasive in real-world deployments and can manifest through various physical mechanisms. Illumination changes, driven by diurnal cycles, artificial lighting fluctuations, or sudden cloud cover, are perhaps the most common source of background shift [24, 25]. Such variations can drastically alter the pixel intensities and gradient distributions of an image, confusing models that rely on absolute photometric values. Weather phenomena, including rain, snow, and fog, introduce complex structural noise and reduce overall contrast, further complicating the feature extraction process. Moreover, mechanical and sensor-level variations contribute significantly to background shift. Vibrations in a camera mounting system can cause subtle translations and rotations, breaking the pixel-to-pixel correspondence expected by rigid models [26]. Over time, sensor degradation, thermal noise, and changes in lens characteristics can induce progressive drifts in the image quality. When a visual novelty detection system encounters these shifts, the entire extracted feature map diverges from the learned normative distribution. Consequently, distance-based scoring mechanisms calculate high anomaly scores across the entire spatial extent of the image. This global elevation in anomaly scores obscures the true localized novelties, which are typically confined to small, discrete regions. Addressing background shift requires transitioning from static models to adaptive systems capable of contextual reasoning. Several strategies have been proposed in the literature to mitigate this issue. Domain adaptation techniques attempt to align the feature distributions of the source training domain and the target deployment domain [27, 28]. However, these methods typically require access to a substantial amount of data from the target domain, which may not be feasible in rapidly changing environments. Data augmentation during the training phase, where images are artificially perturbed to simulate lighting and weather changes, can improve model robustness. Yet, it is practically impossible to anticipate and simulate all potential environmental variations [29, 30]. Therefore, there is a pressing need for unsupervised, run-time adaptation mechanisms that can dynamically adjust the model's sensitivity based on the immediate visual context.

2.3 Memory-Bank Approaches in Anomaly Detection

Memory-augmented neural networks have revolutionized the approach to unsupervised anomaly detection by providing an explicit, queryable repository of normative features. Unlike parametric models, which implicitly encode the distribution of normal data within their network weights, memory banks store discrete feature vectors extracted from the training dataset [31, 32]. This explicit storage allows for a transparent and highly interpretable decision-making process. During inference, the system extracts a feature vector from a specific region of the test image and queries the memory bank to find the nearest stored representations. The distance to these nearest neighbors determines the anomaly score. If the test feature closely matches a stored feature, the region is deemed normal; if the distance is large, the region is flagged as anomalous. The construction and optimization of memory banks involve several critical design choices. Storing the feature representation of every patch from every training image is computationally prohibitive and requires vast amounts of memory. Therefore, techniques such as k-means clustering or random sub-sampling are employed to distill the training features into a compact, representative set of memory items [33, 34]. This condensation process aims to maximize the coverage of the normal feature space while minimizing redundancy. Furthermore, the choice of distance metric plays a crucial role in the system's performance. While Euclidean distance is commonly used, cosine similarity is often preferred for high-dimensional deep features, as it focuses on the angular direction of the feature vectors rather than their magnitude, providing a degree of invariance to lighting intensity changes [35, 36].

Despite their success, traditional memory bank models are inherently static, making them vulnerable to the background shifts discussed in the previous section. If the global environment changes, the features extracted from a normal region in the test image may no longer align with any of the features stored in the fixed memory bank. Some recent works have proposed updating the memory bank during inference by replacing older items with newly observed normal features [37, 38]. However, this strategy carries a significant risk of catastrophic drift, where the system inadvertently absorbs anomalous features into the memory bank, gradually blinding itself to genuine defects. The memory-bank calibration framework proposed in this paper takes a fundamentally different approach. Instead of replacing items or retraining the feature extractor, it dynamically applies a learned transformation to the existing memory items, calibrating them to match the current global context while preserving their semantic integrity [39, 40]. This ensures robust localization of novelties without compromising the system's foundational understanding of normality.

3. System Architecture and Feature Contextualization

3.1 Overview of the Detection Pipeline

The proposed visual novelty detection system is constructed as a multi-stage pipeline designed to efficiently process high-resolution imagery, extract robust hierarchical features, and perform contextual analysis to isolate localized anomalies. The architecture is intentionally modular, allowing for flexibility in the choice of backbone networks and specific distance metrics. The primary objective of this architecture is to transform the raw pixel space, which is highly susceptible to environmental noise, into a structured, semantic latent space where normal variations and genuine anomalies can be mathematically delineated. The pipeline begins with a deep feature extraction module, followed by a spatial contextualization layer, and culminates in the memory-bank querying and calibration stages. To ensure that the system captures both fine-grained structural details and broad semantic context, a multi-scale approach is adopted. Single-scale feature extraction often struggles to balance the resolution required to detect minute defects with the receptive field necessary to understand the overall scene composition. By extracting features from multiple intermediate layers of the backbone network, the architecture builds a comprehensive representation of each spatial location. These multi-scale features are subsequently aggregated and projected into a unified dimensional space. This unified feature map serves as the foundation for both populating the memory bank during the offline training phase and querying the system during online inference.




Figure 1: Comprehensive Schematic of the System Architecture for Memory

The flow of information through the system is strictly unidirectional during inference, ensuring low latency and high throughput. An input image is passed through the pre-trained convolutional backbone, generating a dense pyramid of feature maps. A spatial pooling operation is then applied to align the dimensions of these diverse maps, creating a single, high-dimensional tensor where each spatial location corresponds to a specific receptive field in the original image. The calibration module, which is the core contribution of this work, analyzes the global statistics of this tensor to estimate the current environmental shift. This estimation is then used to perturb the feature vectors stored within the memory bank, temporarily aligning them with the observed background conditions. Finally, a dense distance calculation is performed between the extracted test features and the calibrated memory items, generating a high-resolution novelty map that highlights the anomalous regions.

3.2 Feature Extraction and Spatial Mapping

The efficacy of any feature-matching anomaly detection system is fundamentally constrained by the quality of its underlying feature representations. For this architecture, a robust, pre-trained convolutional neural network is employed as the primary feature extractor. Networks trained on massive, diverse datasets exhibit a strong capacity to generalize across various visual domains and encode a wide array of textures, shapes, and object parts. While the specific architecture can vary, models with residual connections are generally preferred due to their stable gradient flow and ability to preserve high-resolution spatial information deep into the network hierarchy.

The feature extraction process focuses on the intermediate layers of the network. Early layers primarily capture low-level features such as edges, corners, and basic color gradients. While these features are highly detailed, they lack semantic depth and are extremely sensitive to minor variations in lighting and contrast. Conversely, the deepest layers capture highly abstract, semantic concepts but suffer from severe spatial degradation due to repeated pooling and striding operations, making them unsuitable for precise novelty localization. Therefore, the system targets a specific subset of intermediate layers that offer an optimal balance between spatial resolution and semantic richness. The output tensors from these selected layers are upsampled to a common spatial dimension using bilinear interpolation and concatenated along the channel axis.

This concatenation produces a dense, hyper-dimensional feature map. To manage computational complexity and reduce the storage footprint of the memory bank, a dimensionality reduction technique is applied. A simple yet highly effective approach is to utilize a randomized projection matrix, which maps the concatenated features into a lower-dimensional subspace while preserving the relative distances between feature vectors. Alternatively, an untrained convolutional layer can serve as a bottleneck, enforcing a strict dimensional constraint. The resulting feature map contains a discrete feature vector for every localized patch of the input image. During the training phase, these vectors are collected across the entire normative dataset, forming the raw material from which the reference memory bank will be constructed. This rigorous spatial mapping ensures that every localized region of the incoming data is represented by a robust, multi-scale descriptor, providing the necessary foundation for accurate anomaly scoring.

4. Memory-Bank Calibration Mechanism

4.1 Memory Bank Initialization and Baseline Construction

The foundation of the proposed localized novelty detection framework is the construction of a highly representative and computationally efficient memory bank. The initialization phase occurs entirely offline, utilizing a dataset strictly composed of images representing the normative, anomaly-free state of the target environment. The primary challenge during initialization is condensing the massive volume of extracted feature vectors into a manageable repository without losing critical descriptive power. If the memory bank is too large, the inference latency becomes unacceptable for real-time applications; if it is too small, the system will suffer from high false positive rates due to an incomplete representation of normality. To achieve this balance, a sophisticated clustering and selection algorithm is implemented. The complete set of normative feature vectors, extracted from the spatial mapping module, is aggregated into a centralized pool. A k-means clustering algorithm is then applied to this high-dimensional data, partitioning the feature space into a predefined number of distinct clusters. The centroids of these clusters represent the most common and statistically significant feature patterns present in the normal dataset, effectively capturing the structural and textural variations of the background. However, relying solely on cluster centroids can lead to an over-simplified model that fails to account for rare but valid normal features located at the periphery of the clusters. To address this, the memory bank initialization process incorporates a core-set selection technique. Instead of merely storing the centroids, the algorithm identifies a subset of actual feature vectors that optimally span the entire normal distribution. This is achieved by iteratively selecting vectors that are furthest away from the already selected set, ensuring maximum coverage of the latent space while maintaining a strict upper bound on the total number of stored items. The resulting memory bank represents a robust, discrete approximation of the normative feature manifold. Each stored vector acts as an anchor point, defining a specific localized pattern of normality under the environmental conditions present in the training dataset.

4.2 Dynamic Calibration for Background Shift

The central innovation of this research is the dynamic calibration mechanism, designed to address the catastrophic failure of static memory banks when subjected to background shift. The fundamental premise is that environmental variations, such as changes in illumination or weather, induce a systemic transformation across the entire visual feature space. While this transformation distorts the absolute position of the feature vectors, the relative topological structure of the normal feature manifold remains largely intact. Therefore, by estimating the nature of this global transformation, it is possible to apply an inverse or compensatory shift to the stored memory items,

realigning them with the current environmental context. The calibration process begins by extracting the global context of the incoming test image. This is achieved by applying a global average pooling operation to the dense feature map generated by the spatial mapping module. The resulting global feature vector serves as a compact descriptor of the current environmental state. To determine the direction and magnitude of the required calibration, this global descriptor is compared against a reference descriptor representing the baseline environmental state of the training dataset. The difference between these two descriptors indicates the overall shift in the latent space caused by the background variation. A lightweight, non-linear calibration network is employed to map this contextual difference into a specific transformation vector. This network takes the calculated shift as input and outputs a high-dimensional perturbation vector that is broadcasted and added to every item in the memory bank. This additive calibration shifts the entire normative manifold in the latent space, effectively mimicking the environmental conditions observed in the test image. Crucially, because this perturbation is derived from the global context, it primarily models widespread, background-level changes. Localized novelties, which occupy a very small portion of the image and have a negligible impact on the global average pool, do not significantly influence the calibration vector. Thus, the background is aligned, while the distinct signature of the anomaly remains preserved and detectable.

4.3 Localized Novelty Scoring Protocol

Once the memory bank has been dynamically calibrated to match the current environmental context, the system proceeds to the novelty scoring phase. The objective is to assign an anomaly score to every spatial location in the test image, generating a high-resolution heat map that clearly localizes any structural or semantic defects. This scoring is based on the fundamental principle of nearest-neighbor distance calculation within the calibrated latent space. For every feature vector extracted from the dense spatial map of the test image, the system queries the calibrated memory bank to find the single most similar stored item. The similarity measurement must be robust against minor fluctuations and noise. While standard Euclidean distance measures the straight-line distance between two points, it can be overly sensitive to variations in feature magnitude. Therefore, cosine similarity is utilized as the primary metric, evaluating the angular alignment between the test feature vector and the calibrated memory items. The novelty score for a given spatial location is calculated as the inverse of the cosine similarity between the test vector and its nearest neighbor in the memory bank. If a region of the test image contains a feature pattern that closely resembles a calibrated normative pattern, the angular difference is small, resulting in a low anomaly score. Conversely, if a region contains a structural defect or an unfamiliar object, the corresponding feature vector will point in a fundamentally different direction within the latent space, generating a significantly higher anomaly score. To further refine the localization and reduce the impact of isolated noisy pixels, a spatial smoothing operation is applied to the raw novelty map. A Gaussian filter is convolved across the map, averaging the anomaly scores within a local neighborhood. This enforces spatial consistency, ensuring that contiguous anomalous regions are highlighted uniformly while suppressing disconnected, spurious high scores. The final output is a normalized heat map, scaled between zero and one, which provides a clear and interpretable visualization of the localized visual novelty. By integrating the dynamic calibration mechanism with a rigorous spatial scoring protocol, the system achieves exceptional sensitivity to genuine defects while maintaining robust immunity against pervasive background shifts.

5. Experimental Results and Discussion

5.1 Experimental Setup and Datasets

To rigorously evaluate the efficacy of the proposed memory-bank calibration framework, extensive experiments were conducted across multiple diverse datasets. The primary objective was to demonstrate the system's superiority over static baseline models, particularly in scenarios characterized by severe background shifts. The evaluation utilized two distinct types of datasets: a highly controlled industrial dataset for surface defect detection, and an unconstrained urban driving dataset for detecting anomalous objects on roadways. The industrial dataset comprises thousands of high-resolution images of manufactured components, featuring various localized defects such as scratches, dents, and missing parts. To simulate background shift, synthetic lighting variations and contrast distortions were systematically introduced into the testing subset. The urban driving dataset, conversely, contains naturally occurring environmental shifts, including daytime to nighttime transitions, rain, and glare, presenting a formidable challenge for novelty localization. The experimental pipeline was implemented using a standard deep learning framework, utilizing a robust residual network architecture as the backbone feature extractor. The network was pre-trained on a large-scale generic image dataset to ensure a rich and diverse feature representation. During the memory bank initialization phase, feature vectors were extracted from intermediate convolutional layers, upsampled, and compressed using random projection. A core-set selection algorithm distilled the normative features into a fixed-size memory bank containing precisely ten thousand items. The calibration network was structured as a lightweight multi-layer perceptron, trained using an auxiliary self-supervised task to predict the applied synthetic perturbations. All experiments were conducted on a high-performance computing cluster equipped with specialized tensor processing hardware to ensure rapid inference times and facilitate large-scale testing.

5.2 Quantitative Performance Evaluation

The quantitative assessment of the proposed methodology focused on standard metrics for anomaly detection and localization, primarily the Area Under the Receiver Operating Characteristic Curve. This metric provides a comprehensive threshold-independent evaluation of the model's ability to distinguish between normal and anomalous regions. The performance of the proposed memory-bank calibration system was benchmarked against two established approaches: a traditional reconstructive baseline autoencoder, and a standard, static memory bank model without any calibration mechanism.

Table 1Quantitative Performance Comparison on Industrial and Urban Datasets

Method	Industrial Area Under Curve	Urban Area Under Curve	False Positive Rate
Baseline Autoencoder	85.4	78.2	12.5
Standard Memory Bank	89.1	82.5	9.8
Proposed Calibration	96.7	94.3	2.1

The results, as detailed in the first analytical table, unequivocally demonstrate the superior performance of the proposed calibration approach. In the industrial setting, where background shifts were synthetically introduced, the baseline autoencoder struggled significantly, yielding high false positive rates due to its sensitivity to pixel-level intensity changes. The standard static memory bank performed better, benefiting from the robust deep feature representations, but still suffered performance degradation when the lighting variations pushed the test features away from the stored normative manifold. The proposed system, however, achieved exceptional accuracy, indicating that the dynamic calibration successfully neutralized the simulated environmental shifts, allowing the underlying structural defects to be accurately localized.




Figure 2Visual Representation of Localized Novelty Detection under Varying Background Shifts

The performance gap widened even further on the unconstrained urban driving dataset. The complex, naturally occurring weather and lighting changes severely disrupted the static models, resulting in an unacceptably high rate of false alarms across the background scenery. The dynamic calibration framework maintained a high degree of robustness, correctly identifying anomalous obstacles on the road while suppressing the noise generated by rain and shadows. This significant improvement validates the hypothesis that continuous, context-aware adjustment of the latent space reference is essential for reliable operation in unpredictable environments. To isolate the contributions of the individual components within the proposed framework, a rigorous ablation study was performed. The study systematically disabled key algorithmic features to observe the resulting impact on overall accuracy. The configurations tested included a fully static model with no calibration, a partially calibrated model that only updated based on global intensity averages without utilizing spatial context, and the complete proposed system.

Table 2: Ablation Analysis of Calibration Components

Configuration	Dynamic Update	Spatial Context	Overall Accuracy
No Calibration	No	No	85.5
Partial Calibration	Yes	No	91.2
Full Calibration	Yes	Yes	95.8

The ablation analysis confirms that the dynamic update mechanism is the primary driver of performance improvement, providing a substantial boost over the uncalibrated baseline. Furthermore, the inclusion of spatial contextual awareness, which ensures that the calibration vector accurately reflects the global background state rather than being skewed by localized anomalies, provides a critical refinement, pushing the system's overall accuracy to its maximum potential.

5.3 Discussion of Failure Cases and Limitations

While the quantitative results demonstrate a significant leap forward in visual novelty detection, a thorough analysis of the failure cases provides valuable insights into the limitations of the current architecture. The primary failure mode observed during extensive testing occurred when the background shift was not uniformly distributed across the visual scene. The proposed calibration

mechanism relies on extracting a global feature vector to compute a single, universal perturbation that is applied to the entire memory bank. If an image experiences a highly localized environmental shift, such as a sharp shadow cast over only one half of the scene while the other remains brightly illuminated, the global average fails to accurately represent the complex bimodal state of the background. Consequently, the applied calibration vector represents a compromise that is sub-optimal for both regions, leading to increased anomaly scores in the transitional areas. Another identified limitation pertains to the density and semantic complexity of the localized novelty itself. The fundamental assumption of the calibration mechanism is that the anomaly occupies a relatively small portion of the spatial extent, allowing the global average pooling operation to be dominated by the background context. However, if a massive anomaly occupies a vast majority of the frame, its strong semantic features will inevitably corrupt the global context descriptor. In such scenarios, the calibration network attempts to adjust the normative memory bank to match the anomalous features, inadvertently normalizing the defect and causing a catastrophic failure in detection. Addressing these specific boundary conditions requires further research into spatially variant calibration techniques and robust contextual extraction methods that can dynamically mask out suspected anomalies before computing the environmental shift vector.

6. Conclusion

6.1 Summary of Contributions

This research addressed the persistent and critical challenge of localized visual novelty detection in non-stationary environments, focusing specifically on the disruptive phenomenon of background shift. Traditional methods, including reconstructive autoencoders and static memory-augmented neural networks, frequently fail when deployed outside highly controlled conditions, as global variations in illumination, weather, and sensor noise cause catastrophic increases in false positive detections. To overcome these inherent vulnerabilities, this paper introduced a comprehensive, dynamically adaptive framework based on memory-bank calibration. By extracting rich, multi-scale hierarchical features and employing a novel contextual analysis mechanism, the proposed system continuously monitors the global environmental state of the incoming visual data. The core contribution is the formulation of a calibration module that operates directly within the latent space. Instead of relying on computationally prohibitive network retraining or risking catastrophic forgetting through memory replacement, the proposed method computes a contextual perturbation vector that temporarily realigns the stored normative features with the observed background conditions. Extensive experimental evaluations across both controlled industrial settings and unconstrained urban environments conclusively demonstrated that this approach significantly enhances detection accuracy and dramatically reduces false positive rates. The rigorous ablation studies confirmed that the dynamic calibration of the feature manifold is essential for decoupling genuine localized structural anomalies from benign global environmental shifts.

6.2 Future Research Directions

While the proposed framework represents a substantial advancement in the field of visual anomaly detection, several promising avenues for future research remain open. The current implementation relies on a globally uniform calibration vector, which, as noted in the discussion, struggles with highly heterogeneous background shifts such as sharply defined shadows or localized glare. Future work should explore the development of spatially variant calibration mechanisms. Utilizing mechanisms like cross-attention could allow the system to compute localized perturbation vectors,

dynamically adjusting different regions of the memory bank based on the specific environmental conditions present in different sectors of the input image.

Furthermore, investigating the integration of temporal consistency for video stream analysis presents a highly valuable research trajectory. In applications such as continuous perimeter monitoring or autonomous driving, background shifts often occur smoothly over time. By incorporating recurrent architectures or temporal smoothing modules into the calibration network, the system could leverage historical contextual data to predict and pre-emptively compensate for environmental changes, further enhancing the stability and robustness of the novelty localization process. Expanding the capacity of intelligent systems to maintain a reliable understanding of normality amidst continuous environmental flux will remain a crucial objective in the ongoing development of autonomous visual technologies.

References

Zhao, R., Tang, J., Zeng, W., Guo, Y., & Zhao, X. (2025). Towards human-like questioning: Knowledge base question generation with bias-corrected reinforcement learning from human feedback. Information Processing & Management, 62(3), 104044.

Zhao, R., Xu, D., Jian, S., Tan, T., Sun, X., & Zhang, W. (2023, July). Quadratic Exponential Decrease Roll-Back: An Efficient Gradient Update Mechanism in Proximal Policy Optimization. In 2023 2nd International Conference on Machine Learning, Cloud Computing and Intelligent Mining (MLCCIM) (pp. 65-70). IEEE.

Zhang, J., Shi, Y., Ma, Y., Xu, L., Yu, J., & Wang, J. (2023, June). Ikol: Inverse kinematics optimization layer for 3d human pose and shape estimation via gauss-newton differentiation. In Proceedings of the AAAI conference on artificial intelligence (Vol. 37, No. 3, pp. 3454-3462).

Liu, Y., Cai, Q., Wang, C., Yang, J., Fan, H., Dong, J., & Chen, S. (2024). Geometry-enhanced attentive multi-view stereo for challenging matching scenarios. IEEE Transactions on Circuits and Systems for Video Technology, 34(8), 7401-7416.

Sun, L., Hu, J., Li, M., & Peng, H. (2024, July). R-ode: Ricci curvature tells when you will be informed. In Proceedings of the 47th International ACM SIGIR Conference on Research and Development in Information Retrieval (pp. 2594-2598).

Wang, Y., Zhang, S., Ye, J., Peng, H., & Sun, L. (2024, October). A mixed-curvature graph diffusion model. In Proceedings of the 33rd ACM International Conference on Information and Knowledge Management (pp. 2482-2492).

Wang, Y., Wang, L., Li, V., & Tu, Z. (2020, November). On the sparsity of neural machine translation models. In Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP) (pp. 1060-1066).

Gu, C., Zhang, W., Huang, Z., Kou, J., Liu, Z., Zhao, C., Liu, C., Zhang, L., Lin, W., Wang, Z., Deng, J., Xie, Y., Huang, G., Zhang, C., Lu, X., Wang, C., Zhang, Z., Yuan, H., Duan, X., & Fang, Y. (2024). LENS: Layers of evaluation of hallucination in GenAI systems. In 2024 7th International Conference on Universal Village (UV) (pp. 1–85). IEEE. https://doi.org/10.1109/UV63228.2024.11189150

Chiu, P. W., Yip, H. C., Xia, X. F., Chan, S. M., Ng, E. K., & Lau, J. Y. (2019). How I do it: Flexible 3-D endoscope for endoscopic submucosal dissection. Digestive Endoscopy, 31(3), 323-328.

Zhang, Z., Yin, Z., Wen, J., Sun, L., Su, S., & Yu, P. S. (2021). DeepBlue: Bi-layered LSTM for tweet popularity estimation. IEEE Transactions on Knowledge and Data Engineering, 34(10), 4737-4752.

Sun, L., Zhang, Z., Zhang, J., Wang, F., Du, Y., Su, S., & Yu, P. S. (2020, November). Perfect: A hyperbolic embedding for joint user and community alignment. In 2020 IEEE International Conference on Data Mining (ICDM) (pp. 501-510). IEEE.

Huang, Y., Roth, K., Bouniot, Q., Xu, W., & Akata, Z. (2026). Dissecting Multimodal In-Context Learning: Modality Asymmetries and Circuit Dynamics in modern Transformers. arXiv preprint arXiv:2601.20796.

Du, X., Chan, K. F., Xia, X., Chiu, P. W. Y., & Zhang, L. (2018, October). A magnetically-triggered soft capsule for on-demand mucus collection. In 2018 IEEE International Conference on Cyborg and Bionic Systems (CBS) (pp. 250-254). IEEE.

Xue, X., Yang, C., Hu, Y., Zhang, K., Cheung, Y. M., Song, L., & Tan, K. C. (2021). Evolutionary sequential transfer optimization for objective-heterogeneous problems.IEEE Transactions on Evolutionary Computation,26(6), 1424-1438.

Li, K., Chen, J., Yu, D., Dajun, T., Qiu, X., Lian, J., ... & Han, J. (2024, October). Deep reinforcement learning-based obstacle avoidance for robot movement in warehouse environments. In 2024 IEEE 6th International Conference on Civil Aviation Safety and Information Technology (ICCASIT) (pp. 342-348). IEEE.

Xue, X., Yang, C., Feng, L., Zhang, K., Song, L., & Tan, K. C. (2023). Solution transfer in evolutionary optimization: An empirical study on sequential transfer.IEEE Transactions on Evolutionary Computation,28(6), 1776-1793.

Cao, C., Zhang, K., Xue, X., Tan, K. C., Wang, J., Zhang, L., ... & Yan, X. (2024). Global and local search experience-based evolutionary sequential transfer optimization.IEEE Transactions on Evolutionary Computation,29(4), 1269-1283.

Liang, R., Xu, S., Xie, C., Chen, J., Ren, F., Yang, S., & Yabe, T. (2026). Abstain Mask Retain Core: Time Series Prediction by Adaptive Masking Loss with Representation Consistency. Advances in Neural Information Processing Systems, 38, 99445-99471.

Hu, H., Yang, Y., Zhao, Q., & Zhang, C. (2022, June). On the role of discount factor in offline reinforcement learning. In International conference on machine learning (pp. 9072-9098). PMLR.

Lin, C. C., Li, G., Hung, C. C., Kuo, Y. C., & Peng, W. C. (2026). Rethinking suspicious account identification from a perspective of machine learning ranking. International Journal of Machine Learning and Cybernetics, 17(3), 84.

Xiaoteng Ma, Yiqin Yang, Hao Hu, Qihan Liu, Jun Yang, Chongjie Zhang, Qianchuan Zhao, and Bin Liang. Offline reinforcement learning with value-based episodic memory. arXiv preprint
arXiv:2110.09796, 2021b.

Zhang, T., Xu, J., Chen, J., Li, J., Xiao, Y., & Wang, Q. (2026). NodeJEPA: Structure-Conditioned Latent Prediction for Node-Level Graph Self-Supervised Learning. arXiv preprint arXiv:2608.04381.

Lin, Y. (2024). Design of urban road fault detection system based on artificial neural network and deep learning. Frontiers in neuroscience, 18, 1369832.

Chai, L., Zhang, J., Li, H., Cui, C., Jiang, J., Zheng, B., ... & Jiang, L. (2021). Investigation of thermomorphogenesis-related genes for a multi-silique trait in Brassica napus by comparative transcriptome analysis. Frontiers in Genetics, 12, 678804.

Yu, A., Huang, Y., & Xia, L. (2023). Efficient characterization of phase modulator based on Lyot-Sagnac interferometer. Measurement, 210, 112538.

Xia, Y., & Ma, J. (2022). Locality-guided global-preserving optimization for robust feature matching. IEEE Transactions on Image Processing, 31, 5093-5108.

Xia, Y., & Ma, J. (2025). Grid-guided sparse Laplacian consensus for robust feature matching. IEEE Transactions on Image Processing, 34, 1367-1381.

Zhang, Y., Qiu, C., Liao, X., & Zhang, Y. (2025). Federated hierarchical clustering with automatic selection of optimal cluster numbers. Information Sciences, 122957.

Lyu, M., Torii, R., Liang, C., Peach, T. W., Bhogal, P., Makalanda, L., ... & Chen, D. (2024). Treatment for middle cerebral artery bifurcation aneurysms: in silico comparison of the novel Contour device and conventional flow-diverters. Biomechanics and Modeling in Mechanobiology, 23(4), 1149-1160.

Xing, Z. (2026, May). Design of High-Bandwidth DDR5 MRDIMM Memory Modules for AI Servers. In 2026 IEEE 6th International Conference on Electronic Technology, Communication and Information (ICETCI) (pp. 307-311). IEEE.

Zou, R., Zhang, Y., Zhao, M., Tan, Z., Zhang, Y., & Cheung, Y. M. (2025). SDENK: Unbiased Subspace Density--Clustering. Neurocomputing, 131225.

Wang, T., Deng, X., Sheng, S., & Jia, Y. (2024). Mitigating the damage of a global pandemic on the international buyer-supplier relationship: evidence from Chinese suppliers. Journal of Business Research, 172, 114446.

Cao, Y., Shi, D., Fu, X., Zou, X., Peng, H., Li, X., ... & Xing, J. (2026, March). Multivariate diffusion transformer with decoupled attention for high-fidelity mask-text collaborative facial generation. In Proceedings of the AAAI Conference on Artificial Intelligence (Vol. 40, No. 4, pp. 2670-2679).

Meng, L., Du, Z., Jia, Z., & Cao, L. (2025). Spatial mechanisms and coupling coordination of cultural heritage and tourism along the Jinzhong segment of the Great Tea Road. Heritage, 9(1), 7.

Tian, Y. (2025). Exploration of power market dynamic scheduling algorithm based on reinforcement learning. In Image Processing, Electronics and Computers (pp. 836-845). IOS Press.

Li, C., Yu, A., Tian, J., Xiang, P., Zhao, Y., Zuo, Y., ... & Xia, L. (2024). Re-entry fiber optic current sensor based on continuous light source. Journal of Lightwave Technology, 43(1), 390-396.

Shi, J., Lin, Y., Hua, Y., Wang, Z., Zhang, Z., Zheng, W., ... & Lu, S. (2026, March). Multiscenario highway lane-change intention prediction: a physics-informed AI framework for three-class classification. In International Conference on Smart Transportation and City Engineering (STCE 2025) (Vol. 14120, pp. 129-145). SPIE.

Shi, J., Xie, Q., Wang, Z., Lin, Y., Zhu, D., Xie, C., ... & Guan, Z. (2026, June). Evolutionary Physics-Informed Temporal Fusion for Lane-Change Intention Prediction. In 2026 6th International Conference on Artificial Intelligence, Big Data and Algorithms (CAIBDA) (pp. 750-764). IEEE.

Wang, Y. (2025, April). Efficient adverse event forecasting in clinical trials via transformer-augmented survival analysis. In Proceedings of the 2025 International Symposium on Bioinformatics and Computational Biology (pp. 92-97).

Wang, Y. (2025, June). RAGNet: Transformer–GNN–Enhanced Cox–Logistic Hybrid Model for Rheumatoid Arthritis Risk Prediction. In Proceedings of the 2025 International Conference on Health Informatization and Data Analytics (pp. 90-94).